



Am grupa
www.amgrupa.hr • info@amgrupa.hr

 **CREINA** d.d.

KATALOG SEZONA 2019



STANDARDNA OPREMA CREINE JEDNOSOVIINSKE BOJANE:

- podvozje: osovina bez ogibljenja, max 25 km/h
- rezervoar bojan
- kočnica mehanička (R)
- vanjska zaštita od korozije lakirana temeljnom i pokrivnom bojom
- unutarnja zaštita od korozije sa dvokomponentnom crnom zaštitom
- nadtlačni + prelivni sigurnosni ventil + manometar
- usisna cijev PVC + aluminiska, dužine ovisno o izvedbi
- potporna noga mehanička



TIP CREINE:	CV 1200	CV 1700	CV 2200	CV 2700	CV 3200
TIP:	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA
REZERVOAR:	BOJANI	BOJANI	BOJANI	BOJANI	BOJANI
DEBLJINA REZERVOARA:	4 mm	4 mm	4 mm	4 mm	4 mm
ZAPREMINA:	1200 L	1700 L	2200 L	2700 L	3200 L
TIP PUMPE:	DKP 4	DKP 4	DKP 4	DKP 4	DKP 4
PUMPA:	3300 L/min	3300 L/min	3300 L/min	3300 L/min	3300 L/min
OSOVINA DIMENZIJE:	60x1350 - 6	60x1350 - 6	60x1350 - 6	60x1350 - 6	60x1350 - 6
ZASUN:	4" R	4" R	4" R	4" R	4" R
KOČNICE:	R	R	R	R	R
GUME:	11.5/80-15.3 10PR	11.5/80-15.3 10PR	11.5/80-15.3 10PR	11.5/80-15.3 10PR	11.5/80-15.3 10PR
KATALOŠKI BROJ:	108352	102948	103383	103422	103503

STANDARDNA OPREMA CREINE JEDNOSOVIINSKE POCINČANE:

- podvozje: osovina bez ogibljenja, max 25 km/h
- rezervoar pocinčan
- kočnica mehanička (R) + hidraulična (H) iznad CVC 4500
- zaštita od korozije kpl rezervoar vruće pocinčan
- vanjska strana rezervoara dodatno lakirana
- nadtlačni + prelivni sigurnosni ventil + manometar
- usisna cijev PVC + aluminiska, dužine ovisno o izvedbi
- potporna noga mehanička



TIP CREINE:	CVC 2200 V	CVC 2700 V	CVC 3200 V	CVC 4500 V	CVC 5300 V
TIP:	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA
REZERVOAR:	POCINČANI	POCINČANI	POCINČANI	POCINČANI	POCINČANI
DEBLJINA REZERVOARA:	4 mm	4 mm	4 mm	5 mm	5 mm
ZAPREMINA:	2200 L	2700 L	3200 L	4500 L	5300 L
TIP PUMPE:	DKP 4	DKP 4	DKP 4	MEC 400	MEC 500
PUMPA:	3300 L/min	3300 L/min	3300 L/min	4350 L/min	6150 L/min
OSOVINA DIMENZIJE:	60x1350 - 6	60x1350 - 6	60x1350 - 6	70x1700 - 6	70x1700 - 6
ZASUN:	4" R + 4" H	4" R + 4" H	4" R + 4" H	6" RHP + 6" H	6" RHP + 6" H
KOČNICE:	R	R	R	R + H	R + H
GUME:	11.5/80-15.3 10PR	11.5/80-15.3 10PR	11.5/80-15.3 10PR	15/55-17 14PR	500/50-17 14PR
KATALOŠKI BROJ:	171690	171700	171650	171750	171760

TIP CREINE:	CVC 6000 V	CVC 7000 V	CVC 8000 V	CVC 9000 V	CVC 10000 V
TIP:	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA	JEDNOSOVIINSKA
REZERVOAR:	POCINČANI	POCINČANI	POCINČANI	POCINČANI	POCINČANI
DEBLJINA REZERVOARA:	6 mm	6 mm	6 mm	6 mm	6 mm
ZAPREMINA:	6000 L	7000 L	8000 L	9000 L	10000 L
TIP PUMPE:	MEC 800	MEC 800	MEC 800	STAR 60	STAR 60
PUMPA:	8100 L/min	8100 L/min	8100 L/min	10680 L/min	10680 L/min
OSOVINA DIMENZIJE:	80x1800 - 8	100x1800 - 10	100x1800 - 10	100x1800 - 10	100x1800 - 10
ZASUN:	6" RHP + 6" H	6" RHP + 6" H	6" RHP + 6" H	6" RHP + 6" H	6" RHP + 6" H
KOČNICE:	R + H	R + H	R + H	R + H	R + H
GUME:	550/60-22.5 16PR	550/60-22.5 16PR	550/60-22.5 16PR	600/55-26.5 16PR	600/55-26.5 16PR
KATALOŠKI BROJ:	171770	160601	127797	163251	109807

CREINA - tandem pocinčane cisterne dvoosovinske



STANDARDNA OPREMA CREINE DVOOSOVINSKE POCINČANE:

- podvozje: osovina bez ogibljenja, max 25 km/h
- rezervoar pocinčan
- kočnica mehanička (R) + hidraulična (H) iznad CVC 4500
- zaštita od korozije kpl rezervoar vruće pocinčan
- vanjska strana rezervoara dodatno lakirana
- nadtlračni + prelivni sigurnosni ventil + manometar
- usisna cijev PVC + aluminiska, dužine ovisno o izvedbi
- potporna noga mehanička



TIP CREINE:	CVC 8000 VT	CVC 10000 VT	CVC 12000 VT	CVC 14000 VT	CVC 16000 VT
TIP:	DVOOSOVINSKA	DVOOSOVINSKA	DVOOSOVINSKA	DVOOSOVINSKA	DVOOSOVINSKA
REZERVOAR:	POCINČANI	POCINČANI	POCINČANI	POCINČANI	POCINČANI
DEBLJINA REZERVOARA:	6 mm	6 mm	6 mm	6 mm	6 mm
ZAPREMINA:	8000 L	10000 L	12000 L	14000 L	16000 L
TIP PUMPE:	MEC 800	STAR 60	STAR 60	STAR 60	STAR 60
PUMPA:	8100 L/min	10680 L/min	10680 L/min	10680 L/min	10680 L/min
OSOVINA DIMENZIJE:	2 x 80x1850 - 8	2 x 90x1950 - 10	2 x 90x1950 - 10	2 x 100x1950 - 10	2 x 100x1950 - 10
ZASUN:	6" RHP + 6" H	6" RHP + 6" H	6" RHP + 6" H	6" RHP + 6" H	6" RHP + 6" H
KOČNICE:	R + H	R + H	R + H	R + H	R + H
GUME:	16/70-20 16PR	550/60-22.5 16PR	550/60-22.5 16PR	550/60-22.5 16PR	550/60-22.5 16PR
KATALOŠKI BROJ:	165986	166006	166016	166026	166036

CREINA - tandem pocinčane cisterne troosovinske

STANDARDNA OPREMA CREINE TROOSOVINSKE POCINČANE:

- podvozje: osovina bez ogibljenja, max 25 km/h
- rezervoar pocinčan
- kočnica mehanička (R) + hidraulična (H) iznad CVC 4500
- zaštita od korozije kpl rezervoar vruće pocinčan
- vanjska strana rezervoara dodatno lakirana
- nadtlračni + prelivni sigurnosni ventil + manometar
- usisna cijev PVC + aluminiska, dužine ovisno o izvedbi
- potporna noga mehanička



TIP CREINE:	CVC 20000 TRI	CVC 25000 TRI
TIP:	TROOSOVINSKA	TROOSOVINSKA
REZERVOAR:	POCINČANI	POCINČANI
DEBLJINA REZERVOARA:	8 mm	8 mm
ZAPREMINA:	20000 L	25000 L
TIP PUMPE:	STAR 84	WPT
PUMPA:	14420 L/min	WPT
OSOVINA DIMENZIJE:	3 x 100x1950 - 10	3 x 100x1950 - 10
ZASUN:	6" RHP + 6" H	8" RHP + 8" H
KOČNICE:	R	R
GUME:	550/60-22.5 16PR	600/55
KATALOŠKI BROJ:	163231	163231

CREINA - pocinčane cisterne s centrifugalnom pumpom



STANDARDNA OPREMA CREINE JEDNOOSOVINSKE POCINČANE:

- podvozje: osovina bez ogibljenja, max 25 km/h
- rezervoar pocinčan
- raspršivač gnojnice pocinčan, top 3" hidraul. okret 360
- kočnica mehanička (R) + hidraulična (H)
- zaštita od korozije kpl rezervoar vruće pocinčan
- vanjska strana rezervoara dodatno lakirana
- nadtlračni + prelivni sigurnosni ventil + manometar
- usisna cijev PVC + aluminiska, dužine ovisno o izvedbi
- potporna noga mehanička



TIP CREINE:	CGKC 2200 V	CGKC 2700 V	CGKC 3200 V	CGKC 4500 V	CGKC 6000 V
TIP:	JEDNOOSOVINSKA	JEDNOOSOVINSKA	JEDNOOSOVINSKA	JEDNOOSOVINSKA	JEDNOOSOVINSKA
REZERVOAR:	POCINČANI	POCINČANI	POCINČANI	POCINČANI	POCINČANI
DEBLJINA REZERVOARA:	4 mm	4 mm	4 mm	5 mm	5 mm
ZAPREMINA:	2200 L	2700 L	3200 L	4500 L	6000 L
TIP PUMPE:	MEC 300	MEC 300	MEC 300	MEC 400	MEC 800
PUMPA:	3600 L/min	3600 L/min	3600 L/min	4350 L/min	8100 L/min
TIP CENTRIFUG. PUMPE:	GARDA 3500	GARDA 3500	GARDA 3500	GARDA 6500	GARDA 6500
PUMPA:	1600 L/min	1600 L/min	1600 L/min	2100 L/min	2100 L/min
OSOVINA DIMENZIJE:	70x1700 - 6	70x1700 - 6	70x1700 - 6	70x1700 - 6	80x1800 - 8
ZASUN:	4" RHP + 4" H	4" RHP + 4" H	4" RHP + 4" H	6" RHP + 6" H	6" RHP + 6" H
KOČNICE:	R + H	R + H	R + H	R + H	R + H
GUME:	15/55-17 10PR	15/55-17 10PR	15/55-17 10PR	15/55-17 10PR	550/60-22.5 16PR
KATALOŠKI BROJ:	156173	157093	146954	167033	145579

CREINA - zamjenski rezervoari bojani i pocinčani

STANDARDNA OPREMA CREINE REZERVOARA:

- opremljeni navarenim nosačima osovine, crpke i rude
- uvaren prelivni ventil, straga kpl poklopac
- na poklopcu 1 predpriprema 4" sa navojem (do 3200)
- odnosno 2 predpripreme sa prirubnicom (od 4500)
- rezervoari imaju unutarnji i vanjsku zaštitu od korozije



KATALOŠKI BROJ	MODEL CREINE	TIP REZERVOARA	ZAPREMINA
156350	CV 1200	BOJANI	1200 L
156360	CV 1700	BOJANI	1700 L
156370	CV 2200	BOJANI	2200 L
156380	CV 2700	BOJANI	2700 L
156390	CV 3200	BOJANI	3200 L

KATALOŠKI BROJ	MODEL CREINE	TIP REZERVOARA	ZAPREMINA
156371	CVC 2200	POCINČANI	2200 L
156381	CVC 2700	POCINČANI	2700 L
156391	CVC 3200	POCINČANI	3200 L



Am grupa
www.amgrupa.hr • info@amgrupa.hr

Am Centar BUZET

Riječka 8 • 52420 Buzet
Tel. +385(0)52 662623 • Fax. +385(0)52 694084
info@amgrupa.hr

Am Centar POREČ

Facinka bb • 52440 Poreč
Tel. +385(0)52 496300 • Fax. +385(0)52 496303
porec@amgrupa.hr

Am Centar VODNJAN

Istarska 159 • 52215 Vodnjan
Tel. +385(0)52 255200 • Fax. +385(0)52 255203
vodnjan@amgrupa.hr

Am Skladište BUZET

Mažinjica bb • 52420 Buzet
Tel. +385(0)52 662623 • Fax. +385(0)52 694084
info@amgrupa.hr

www.amgrupa.hr